


## INS300 IPPBX

### Enterprise-grade Unified Communications for small business

INS300 IPPBX is a embedded hybrid IP PBX specially designed to bring enterprise-grade Unified Communications and Security protection features to small business in a easymanage fashion.It offers up 300 users which offers the flexibility of integration of PSTN lines, GSM Channels and VoIP trunks. It offers a solution for converged voice, video, data, fax and mobility applications out of the box without any extra license fees or recurring costs.



● Strongest-possible security

### Key Benefits

- Customizable combination of FXO, FXS, GSM, modules
- Easy to manage via web-based configuration interface
- Deliver enterprise-grade communication features and functionality to SMBs
- Perfect interoperability with a wide range IP Phone
- 16 FXO ports, or 16 FXS ports, or 8 GSM ports
- no future licensing fees

- protection using SRTP, TLS, and HTTPS
- Energy Saving, Embedded system with low power consumption for your green office
- Flexible dial plan and Manipulation Rules

### Faxes

- T.30, T.38 Faxes
- Fax to Email
- Incoming fax tone detection

## System Capacity

- 300 IP Phone users
- 50 concurrent calls

## Voice Processing

- Protocol: SIP(RFC3261),IAX2
- Transport: UDP, TCP, TLS, SRTP
- DTMF Mode: RFC2833, SIP INFO, In-band
- Voice Codecs: G.711 (alaw/ulaw), G.722,G.726, G.726aal2,G.729A, GSM, ADPCM, Speex, ilbc,H263,H264
- Echo Cancellation: ITU-T G.168 LEC

## PBX Features

- Call forward
- Call transfer
- Call waiting
- Call back
- Call routing
- Call ID
- DND
- DISA
- Conference
- Queue
- Ring group
- Paging/Intercom
- Voicemail
- Voicemail to Email
- IVR
- CDR
- Blacklist
- Music on Hold
- Office hours

- Auto Provisioning
- Call Recording

## Interface

- 16 FXO ports, or 16 FXS ports, or 8 GSM ports
- Single or dual 10/100Mbps RJ45 Ethernet port(s)
- Peripheral Ports: USB
- LED indicators: POWER, Run, Network, PSTN
- Reset button

## Network Features

- Network Protocol: UDP, TCP, TFTP, HTTP, SSH,RTP,SRTP,ARP,NTP
- NAT Traversal: Static NAT, STUN
- HTTP/HTTPS web server
- Digest authentication using MD5
- Static Route
- OpenVPN
- VLAN
- QoS/ToS
- DDNS
- Firewall

## Maintain & Upgrade

- Web based configuration
- Configure backup/restore
- Firmware upgrade by Upload /TFTP
- Web login password modify
- Blacklist

- Packet Capture
- IVR Customization
- Text to Wav
- Call Detail Record (CDR)
- System Logs
- SMTP
- Factory reset,Reboot
- Ping

### **Physical Properties**

- Power Supply: DC 12V, 3.0A (Input:AC100-240V,50-60Hz)
- Power Consumption:23W
- Temperature(Operation): 0 °C ~50 °C  
(Storage): -20 °C ~80 °C
- Operation Humidity: 10%-90% No  
Condensation
- Dimension(W/D/H): 323\*197\*44.5mm